

PROTECTION FRAMEWORK EN 343: 2019

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

For professional use: **Fishing - agriculture - industry - cleaning** or other activities requiring this kind of protection.

PERFORMANCE  ⁴₁ (limited wearing time)
x

The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance $\geq 20,000 \text{ Pa} = \text{Class 4}$
- Evaporative resistance = n/a
Ret $> 40 \text{ m}^2 \cdot \text{Pa} / \text{W} = \text{Class 1}$

RESTRICTIONS ON USE

(specified in the EN 343: 2019 standard)

"A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

Ambient work temperature in °C	Time in minutes
25	60
20	75
15	100
10	240
5	Unlimited

PRINCIPAL MATERIALS

Classic fabric - 460 g/m²

Composition: 80 % PVC – 20 % Polyester
Double-sided coating
+ polyethylene foam inside upper section

Features:

- **WATERPROOF**
- **TOUGH**

INSTRUCTIONS

- CARE



- STORAGE

- Do not leave in package in damp surroundings.
- Store in dry surroundings at room temperature.
- Keep away from strong heat and flames.

ILLUSTRATION AND INSTRUCTIONS

ISOLATECH technique (patented) reducing condensation under the all-weather gear



Snap-fastening elasticated cuffs with gusset



"MAGIC" hood (patented) that moves with the head

Allows the wearing of a hard hat under the hood.



Heavy-duty zip fastener beneath double self-grip flap



For maximum protection, the ISOCLAS jacket can be worn with PPE classed trousers or bib & braces.

SIZE TABLE

Size	Size of the person's body (in cm)		Guideline measurements of clothing (in cm)
	Stature	Chest size	Chest size
S	165-170	86-94	130
M	170-180	94-102	138
L	175-185	102-110	146
XL	180-190	110-124	152
XXL	185+	124-134	160



Colour: yellow

Sizes: S – M – L – XL – XXL

The lifespan of the garment is linked to conditions of use and the quality of its care.