



PROTECTION FRAMEWORK

EN ISO 12402-6 : 2020 – Personal flotation device - Part 6 : Special application lifejackets and buoyancy aids – Safety requirements and additional test methods.

PERFORMANCES

Floatation

Inflatable buoyancy of 165 Newton's in a single chamber.



Inflation system

One automatic, with manual backups, inflator mechanism United Moulders Pro Elite.

Safety Data

Each lifejacket contains 1 cylinders containing 33 grams of compressed Carbon Dioxide CO².

CHARACTERISTICS

- **Colour** : Black / Neon yellow
- **Size** : unique. Suitable for people from 40 kg to 120 Kg, and from 70 cm to 140 cm chest circumference.

DIMENSIONS

- Height : 55 cm
- Width : 30 cm
- Weight : 1,1 Kg

MATERIAL

Polyurethane coated nylon

CARE

- Do not machine wash or tumble dry
- Do not dry clean
- Do not iron
- Hand wash the jacket
- Rinse in fresh water

STORAGE


- Do not leave in package in damp surroundings.
- Store in a dry, well-ventilated place.
- Keep away from strong heat and flames.

THIS ARTICLE IS A

CATEGORY 3 PPE

And complies with EU regulation 2016/425 on Personal Protective Equipment

ILLUSTRATION



Manual inflator



Cartridge viewing window



Crotch strap

Accessory : safety whistle

Optional accessory : automatic emergency eight (MED/SOLAS approved)

i Service / inspection

- ▶ For leisure use : an inspection is recommended every 2 years.
- ▶ For professional use : a full-service inspection at least annually in a certified service station.

Lifejackets should have a daily inspection before wear by the user.

Service life expectation: Ten years maximum (Unless declassified by the service station).

The lifespan of the garment is linked to conditions of use and the quality of its care.